

"PTech" curve hood offers dual placement options, no drawcord



Tonal "ATC" embroidery at front left hip

Great location for logo placement

THE AUTHENTIC T-SHIRT COMPANY® PTech Fleece Youth Hooded Sweatshirt Y220

Product Features:

- 12-oz, 100% polyester double-knit fleece
- Special "ATC" panel hood for easy decoration
- Partial self fabric neck taping
- Set-in sleeves
- 2-panel hood with no drawstring
- Front pouch pocket
- Partial 1x1 rib knit on cuffs
- 1x1 rib knit waistband
- Reinforced topstitching throughout
- "ATC" locker loop neck label

Youth sizes **S (6-8), M (10-12), L (14-16), XL (18-20)**

Corresponding styles:

- F220 – PTech Fleece Hooded Sweatshirt
- F2201 – PTech Fleece VarCITY Hooded Sweatshirt
- Y2201 – PTech Fleece VarCITY Hooded Youth Sweatshirt
- F221/L221/G221 – PTech Fleece Jacket
- F222 – PTech Fleece Track Jacket
- F223/L223/Y224 – PTech Fleece Pant

Fabric Detail:



Fabric Features:



Available Colours and PMS Colours

Textile fabric colours are subject to dye lot variation and will not be exact match to print pantone reference

Black	Sport Heather Grey	True Navy	Charcoal Heather	True Royal
Black 6C	N/A	539C	Multiple shades of 425C	7687C



Y220 - The Authentic T-Shirt Company® PTech™ Fleece Hooded Youth Sweatshirt

GARMENT MEASUREMENTS

Size	S	M	L	XL
Chest - <i>Half Measure</i>	15 1/2"	17"	18 1/2"	20"
Chest - <i>Full Measure</i>	31"	34"	37"	40"
Body Length from HPS	23"	24"	25 1/2"	27"
Sleeve Length from CB	27"	29"	30 3/4"	32 1/2"

Finished measurements in inches. Refer to How to Measure guide for detailed information on measurement instructions.

YOUTH General Sizing Guide

Size	S	M	L	XL
Numeric Size	6-8	10-12	14-16	18-20
Chest	26"-28"	28"-30"	30"-32"	32"-35"
Waist	23"-24 1/2"	24 1/2"-25 1/2"	25 1/2"-27"	27"-29"
Sleeve Length-CB	25"-26"	26"-27 1/2"	27 1/2"-29"	29 1/2"-31"



PRINTING INSTRUCTIONS FOR POLYESTER WICKING FABRICS

Due to the nature of 100% polyester performance fabrics, special care must be taken throughout the printing process. Here are some tips to effectively decorate our performance products.

- Garment temperature must not exceed 320°F or 160°C. Exceeding this temperature will cause the fabric to shrink, become wavy or cause dye migration.
- Dryer temperature and belt speeds must be changed accordingly for polyester fabric.
- If flashing these garments, do not exceed 1-2 seconds. Anything longer may damage the fabric as stated above.
- **Screen Printing:** These garments require the use of poly inks that cure at a lower temperature. A Dyno Grey base blocker on all colours and a second white base blocker on all dark colours are recommended. Please consult your ink supplier for more information.
- Polyester requires a longer cooling time than cotton. Avoid overlap of garments and screen-print/heat transfer until the garments are cooled. Failure to cool the fabric prior to stacking into a printer's fold may cause the fabric and applied ink to stick together.
- **Heat Transfers:** Poly mark heat transfers need to be created with an anti-migration layer in the design. This process can only be done on white or very light coloured fabric. Inks used in printing paper design needs to be darker than the base fabric or colour will migrate with the fabric colour resulting in a bleeding effect.
- **Sublimation Printing:** As noted for the poly mark heat transfers, this process can only be done on white or very light coloured fabric. Inks used in printing paper design needs to be darker than the base fabric or colour will migrate with the fabric colour resulting in a bleeding effect.
- If you heat press these garments, you must adjust the time, temperature and pressure. Failure to do so may damage the fabric as stated above.
- A test sample run is recommended, especially if you have a large order or if your printer does not specialize in printing on performance fabrics.